

DISCLAIMER

Reference herein to any specific commercial company, product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the Department of the Army (DoA). The opinions of the authors expressed herein do not necessarily state or reflect those of the United States Government or the DoA, and shall not be used for advertising or product endorsement purposes.

DISTRIBUTION STATEMENT A. Approved for public release, distribution is unlimited. OPSEC # 23239



CONVOY ACTIVE SAFETY TECHNOLOGY

ENVIRONMENTAL UNDERSTANDING AND
NAVIGATION WITH USE OF
LOW COST SENSORS

Report Documentation Page			Form Approved OMB No. 0704-0188		
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 07 AUG 2012		2. REPORT TYPE Briefing		3. DATES COVERED 01-07-2012 to 01-08-2012	
4. TITLE AND SUBTITLE CONVOY ACTIVE SAFETY TECHNOLOGY (CAST) PRESENTATION			5a. CONTRACT NUMBER		
			5b. GRANT NUMBER		
			5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S) Bernard Theisen			5d. PROJECT NUMBER		
			5e. TASK NUMBER		
			5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army TARDEC, 6501 East Eleven Mile Rd, Warren, Mi, 48397-5000			8. PERFORMING ORGANIZATION REPORT NUMBER #23239		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army TARDEC, 6501 East Eleven Mile Rd, Warren, Mi, 48397-5000			10. SPONSOR/MONITOR'S ACRONYM(S) TARDEC		
			11. SPONSOR/MONITOR'S REPORT NUMBER(S) #23239		
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES Submitted to 2012 NDIA Ground Vehicle Systems Engineering and Technology Symposium August 14-16 Troy, Michigan					
14. ABSTRACT Briefing Charts					
15. SUBJECT TERMS CONVOY ACTIVE SAFETY TECHNOLOGY					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Public Release	18. NUMBER OF PAGES 11	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			



Introduction

ROBOTIC SYSTEMS



- CAST Background
- System Description
- Low Cost Sensor Fusion
- Vehicle Detection
- Vehicle Tracking
- Trajectory Generation
- PVF General Results
- Conclusion

CAST Background

ROBOTIC SYSTEMS

Capabilities

- Improved Operator Safety and Security:
 - Eliminates Rear-End Collisions
 - Reduces Fatigue & Eliminates Road Departures
 - Enables Hands-Free Response to Attack
 - Reduces Collateral Damage to Civilian Population
 - Improved Operator Situational Awareness:
 - Increased IED Detection Rate
 - Ability to Detect Threats at Greater Distance
 - Automated Obstacle Detection and Avoidance
 - Fully Operational Across Typical Mission Needs at speeds consistent with human operators
 - Autonomous multi-vehicle convoys for March Units up to 25 vehicles
 - AutoMate™ kit still allows for manual operation of any tactical wheeled vehicle
 - Ability to maintain convoy speeds consistent with human operators
- Flexibility to Commander in field
- Fast, <10 sec, convoy configuration Ability to change parameters on the fly

History & Status

- Initiated by TARDEC (2005) on Very Limited Budget
- Conducted Initial Feasibility Demonstrations:
 - Fort Carson (February 2006)
 - Fort Gordon (November 2006)
- Conducted Extensive Warfighter Experiments:
 - Fort A.P. Hill (November 2007)
 - Nevada Automotive Test Center (November 2008)
 - Fort Hood (Robotics Rodeo) (September 2009)
 - Fort Benning (September 2010)
- Specified in Operational Needs Statement:
 - Validated & Signed by Dep Chief of Staff (Nov 2009)
- CAST forms basis of AMAS JCTD

CAST Vehicle Capabilities


ROBOTIC SYSTEMS

Vehicle Following



—Follow the preceding vehicle by fusing video and radar data to plan a safe path-following trajectory

Road Following




—Maintain safe trajectories on both primary and secondary roadways by sensing road geometry

Interval Maintenance



—Maintain a safe following distance behind the preceding vehicle and eliminate rear-end collisions


Obstacle Detection & Avoidance



—Sense and avoid static and dynamic obstacles that are near or move to intercept a planned trajectory

System Description


ROBOTIC SYSTEMS



Low Cost Sensor Fusion

ROBOTIC SYSTEMS


- Sensor price point < \$1,000
- Select sensors that cover maximum FOV
- Sensor's failure mechanisms overlapped by operation envelope of other sensors



Vehicle Detection


ROBOTIC SYSTEMS

- Real Time Kinematic Ground Truth of sensor measurements shows sensor performance
- No single sensor has full or even adequate detection of vehicle



Sensor	Reliable Measurements	Reliable %	Unreliable Measurements	Unreliable %	Error Avg	Error Dev	Error Max
Camera	2766	16.10%	14416	83.90%	0.9	0.33	2.63
RADAR	7018	97.69%	166	2.31%	0.89	0.42	5.65
GPS	12880	74.49%	4412	25.51%	0.23	0.26	1.96
LVD	8476	93.38%	139	1.61%	0.96	0.32	2.41


- Use Multiple Kalmans, One for Each New Sensor Measurement
- These Kalman Filters Represent Multiple Hypotheses Of The Lead Vehicle's Position, Speed, Heading, And Steering Radius.
- On Subsequent Input Cycles, Update Hypotheses
- Select Track Based on History, Lead Vehicle State, Number of Recent Supporting Measurements




- The last step is to output a trajectory representing all past estimates of leader position.
- If the Trajectory Can Be Approximated as a Good Estimate of Leader Tran Relative Trajectory, Best Path is a Transform into Follower's Tran Relative Frame
- Otherwise, PVF Generates a Trajectory by Smoothing and Filtering the Path of Previous Leader Position Estimates i.e., “Best” Kalman States Generated from Sensor Measurements.

PVF General Results

ROBOTIC SYSTEMS



Ignoring false positives
from camera



Ignoring false positives
from radar

- The Use of Low Cost Sensors Can Provide an Effective Solution
 - Using Multiple, Over Lapping Sensors with Exclusionary Failure Mechanisms
 - Knowledge of Sensor Performance and Associated Covariance
 - Specifically Tuned to Solve Specific Problem
- CAST Provides a Feasible Solution to Relieve the Soldier of Driving in Order to Focus on Other Tasks